





HPD3. Optical multisensors now also available for ceilings.

The highly sensitive optical system of the HPD3 doesn't just detect people's presence – it counts them, too. In combination with the built-in temperature and humidity sensors, this enables even more precise control of heating, ventilation and air conditioning in conference rooms and offices. In the field of FlexDesk management, the STEINEL HPD sensors provide a solid platform from which you can start optimising the use of space in your buildings.













 professional line

 <p>Counts the number of people present</p>	 <p>Temperature measurement</p>	 <p>Air humidity measurement</p>	 <p>IP interface (Power over Ethernet)</p>
--	--	---	---

Optical sensor

HPD 3



 <p>Number of people</p>	 <p>10 individually definable detection zones</p>	 <p>110° built-in high-frequency sensor</p>	 <p>max. 10 m</p>	 <p>Air humidity</p>
 <p>Temperature</p>	 <p>Brightness</p>	 <p>Bluetooth interface</p>	<p>HPD3 technical specifications</p> <p>Mounting height 2,30–5,00 m</p> <p>Mounting site Ceiling</p> <p>Application, location Indoors</p> <p>Sensor technology high-frequency</p> <p>Detection zones 10 individually definable</p> <p>Reach, radial 10 m (avg.)</p> <p>Angle of coverage 110°</p> <p>Teach function Yes</p> <p>Twilight setting 2-2000 lx</p> <p>Settings via Bluetooth, web interface</p> <p>IP rating IP20</p> <p>Ambient temperature 0-40°C</p> <p>Manufacturer's warranty 5 years</p> <p>Application, room Lecture theatre, classroom, open-plan office, conference room, recreation room, production facilities, dining room/canteen</p> <p>Order details</p> <p>HPD 3 concealed wiring 4007841 067304</p> <p>HPD 3 surface-mounted 4007841 067298</p>	
 <p>HPD 3 as wall-mounted version</p>	 <p>IP interface (MQTT, REST, API, BACnet)</p> 